

SL - TESTER



**THIS SENLAB TESTER IS READY TO USE PACKAGE :
PLUG & PLAY, AND INCLUDES HARDWARE, SOFTWARE AND 3G CONNECTIVITY**

The Senlab tester allows to define local LoRaWAN network coverage with high reliability (with same devices and same gateway as deployment site).

You only need a mobile phone check status in live, by SMS!



TYPICAL APPLICATIONS

- Indoor and/or Outdoor site
- Radio Range testing on a new site
- Devices and gateway position validation
 - Smart and Efficient implementation
- POC to massive deployment acceleration
 - Environment influence checking

Package Content:

- 1 full GW
- 1 outdoor SLtester device
- 1 indoor SLtester device
- 3 years service subscription (around 2000 feedback SMS)
- collecting field help documents

TECHNICAL SPECIFICATIONS

Physical dimensions	250 x 150 x 60 mm
Weight	500 gr
Operating temperature	Indoor 0°C to +55°C / Outdoor -20°C to 70°C
RF sensitivity	-137 dBm
RF power	+14 dBm (25 mW)
Radio band	868 MHz
EMC compliance	ETSI EN 301 489-1, ETSI EN 301 489-3, EN 61000-6-2
Radio compliance	EN 300 220-1 V 2.4.1 (2012-05), EN 300 220-2 V 2.4.1 (2012-05)
Magnetic field exposure	EN 62479
Safety	IEC 60950-1